(11)Publication number:

09-102678

(43) Date of publication of application: 15.04.1997

(51)Int.CI.

H05K 3/46

H05K 9/00

// H05K

1/02

(21)Application number: 07-256275

(71)Applicant : IBIDEN CO LTD

(22)Date of filing: 03.10.1995 (72)Inventor: MORI YOJI


KAWAMURA YOICHIRO

(54) MULTI-LAYER PRINTED CIRCUIT BOARD

(57)Abstract:

PROBLEM TO BE SOLVED: To make a signal line shielded surely by a ground layer from electromagnetic waves, by separating a mounted pad connected to the signal layer into a plurality of sections by a pattern layer that includes a mounting pad connected to the ground layer.

SOLUTION: A ground layer 6 and a signal layer 2 are laminated with an insulating layer in between on a board 1. A mounting pad connected to a ground layer 6 and a mounting pad connected to the signal layer 2 are formed on the face of laminated layer. In this case, the mounting pad is connected through a via hole 4 to the ground layer, and at the same time a soldered body is preferably formed at the mounting pad that is located at the via hole 4. The other mounting pad is connected to the signal layer 2 through the via hole 4, and a soldered body is preferably formed at the mounting pad located at the via hole 4.



LEGAL STATUS

[Date of request for examination]

11.06.1999

[Date of sending the examiner's decision of rejection]

Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

Date of extinction of right

Copyright (C); 1998,2000 Japanese Patent Office

AVAILABLE COP